

PRODUCT DATA

Date: May 2007

Code: 03306/25

IDENDEN TAPE SEAL ADHESIVE 10-63

Idenden Tape Seal Adhesive 10-63 is a water borne co-polymer emulsion adhesive designed for bonding 50 mm woven glass cloth tape over the joints of Mineral Wool Marine Board. This insulation has a special resin impregnated glass cloth facing. Idenden Tape Seal Adhesive 10-63 is white in colour, and is supplied as a brushing grade liquid. It dries translucent and, when dry, is highly water resistant and flame resistant.

Features

- Safer and easier to use than solvent based adhesives
- Water resistant when dry
- Wide service temperature range
- Flame resistant

Product Characteristics

Colour	White
Form	Brushing grade liquid
Weight per litre	1.13 kg
Composition	Co-polymer emulsion. Solids content 45% by volume
Packaging	5 litre polybucket
Shelf life/storage	At least 12 months from date of manufacture when stored unopened in a cool, dry place within the temperature range +5°C to +25°C and out of direct sunlight. PROTECT FROM FROST

Typical Performance Data (approx.)

Drying time	<i>Touch:</i> 2 hours <i>Through:</i> 24 hours
Service temperature	-10°C to +90°C
Application temperature	Above +5°C
Reaction to fire	<i>Wet:</i> Non flammable <i>Dry:</i> Flame resistant
Coverage	60 linear metres of 50 mm tape, or 3 square metres per litre
Solvent for cleaning up	<i>Wet:</i> Water <i>Dry:</i> White spirit

Directions for use

IMPORTANT

Before embarking on any work involving Idenden Tape Seal Adhesive 10-63, the separate Safety Data Sheet should be carefully studied by those carrying out the work.

1. Surfaces should be clean, dry and free from dust and any loose materials.
2. Idenden Tape Seal Adhesive 10-63 should be stirred thoroughly before use.
3. Brush a liberal coating of Idenden Tape Seal Adhesive 10-63 onto the insulation boards along the joint and to 40 mm either side of the joint.
4. Embed a strip of 50 mm glass cloth tape into the wet adhesive and rub it well down, particularly at the edges, to ensure some adhesive penetrates the cloth.
5. A further coat of adhesive should then be brushed over the outside of the tape and worked well in.
6. Smooth away any wrinkles while the adhesive is still wet.
7. Clean application equipment and remove excess adhesive immediately with water.

Precautions in Use

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate health and safety data sheet for Idenden Tape Seal Adhesive 10-63.

This Product Data Sheet covers just one of a large range of products supplied by Bostik Limited. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This Product Data Sheet supersedes all previous technical information on this product, and users of it are cautioned to ensure that it is the current issue. Destroy all previous Product Data Sheets, and if any doubt, contact Bostik Limited, quoting the code number in the top right hand corner on the front of this document. This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.