



TEMATI

SCRIMTEX™



Reinforcement Scrim

- Mastic reinforcement
- Dimensional stability
- Easy to bond

Engineered
Solutions



TEMATI

P.O. Box 1005, 1940 EA Beverwijk,
The Netherlands

Tel. +31 (0) 251 22 91 72

Fax +31 (0) 251 21 23 80

Website: www.temati.com

E-mail: temati@temati.com

SCRIMTEX™ (10 x 10)

SCRIMTEX™ is a 100% fiberglass scrim fabric, especially for mastic reinforcement.
SCRIMTEX™ is coated with a weavelock, in order to give the fabric dimensional stability.

SCRIMTEX™ is used as a jointing tape for plasterboard, as a covering for pipe insulation and as a reinforcement for FOSTER® mastics and coatings used over pipe coverings and insulation.

Product specifications	
Weight	: 58 gr/m ²
Thickness	: 0.20 mm
Construction	: Setting/cm : 3.8 x 3.9 Warp/tex : EC9 - 2 x 34 Weft/tex : EC9 - 68
Tensile strength (warp x weft)	: 85 x 75 daN / 5 cm
Weave	: Leno
Max. application temperature	: 300°C
Fire classification	: M-0
Rollsizes (standard)	: 100 cm x 50 m (= 50 m ² per roll) : 16.5 cm x 50 m (= 8.25 m ² per roll)

MAST-A FAB®

WHITE REINFORCING MEMBRANE

MAST-A-FAB® has a synthetic fiber composition that provides for significantly greater elongation, recovery and freedom from stress breakage.

MAST-A-FAB® has a leno weave that gives stability to the fabric, eliminating the thread movement and distortion inherent to plain weave cloths. It will not detectably affect the flame spread and smoke developed ratings of the selected mastic or coating. MAST-A-FAB® is easy to bond to and wets out readily compared to glass cloth. This minimizes the possibility of disbanding of tack and finish coats. Because it weighs only 0.9 ounces per square yard, about half the weight of glass cloth, Mast-a-Fab is easy to work with. A full roll can easily be "one handed" for a faster, trouble free installation.

MAST-A-FAB® contains no asbestos, lead, mercury, or mercury compounds.

Product specifications	
Color	: white
Composition	: Polyester with PVA Finish
Weave	: Leno
Visual Mesh	: 9 x 8 (openings per square inch)
Elongation	: 70% - 90 % (in waterbase mastic)
Service Temperature	: 121°C maximum
Average Weight	: 0.9 oz/sq. yard (30.5 gr/m ²)
Thread Construction	: 18 ends, 8 picks
Standard roll size	: 30" x 600 feet, 1500 sq.ft. (76 cm x 183 m) (139 sq.m)
Weight per roll (Typical)	: 10 pounds (4.5 kg)
Roll diameter (Typical)	: 6 ¾ inches (17.1 cm)

Engineered
Solutions



P.O. Box 1005, 1940 EA Beverwijk,
The Netherlands
Tel. +31 (0) 251 22 91 72
Fax +31 (0) 251 21 23 80
Website: www.temati.com
E-mail: temati@temati.com